



## DK Cable glands



Cable glands designed to attach and secure the end of a cable to the equipment. Made of very resistant, self-extinguishing, free from halogen and phosphorus material. Easy to assemble.

### Special features:

- Material: polyamid PA66
- Working temperature from -40°C up to 100°C
- Protection degree IP68
- Burning flammability class UL94V-2
- Available sizes: PG7-PG48 and M12-M40
- Available in gray (RAL 7035) and black (RAL 9005) colours
- Nut has an integrated anti vibration protection



Symbol	Metric thread	Ø [mm]	Colour	L1 [mm]	L2 [mm]	ØA [mm]	ØB [mm]	ØC [mm]	ØB1 [mm]	Wires range
DK_M-12-C/1	M12×1.5	12	black	8	4,7	17	15	16	7,5	3-6,5
DK_M-12-S/1			gray							
DK_M-16-C/1	M16×1.5	16	black	8	5	22	18,5	19	9	4-8
DK_M-16-S/1			gray							
DK_M-20-C/1	M20x1.5	20	black	9	5	25	23	24	13	6,7-12
DK_M-20-S/1			gray							
DK_M-25-C/1	M25×1.5	25	black	10	6	30	29	29	17,7	13-16
DK_M-25-S/1			gray							
DK_M-32-C/1	M32×1.5	32	black	11	6,5	39	37	35	21,8	18,5-21
DK_M-32-S/1			gray							
DK_M-40-C/1	M40×1.5	40	black	18	7	50	45	45	30	23-32
DK_M-40-S/1			gray							

Symbol	PG thread	Ø [mm]	Colour	L1 [mm]	L2 [mm]	ØA [mm]	ØB [mm]	ØC [mm]	ØB1 [mm]	Wires range
DK_PG-7-C/1	7	12,2	black	7,5	4,7	18	15	16	7,5	3-6,5
DK_PG-7-S/1			gray							
DK_PG-9-C/1	9	15,3	black	8	5	22	18,5	19	9	4-8
DK_PG-9-S/1			gray							
DK_PG-11-C/1	11	18,3	black	8	5	23	21,5	21,5	11	5-10
DK_PG-11-S/1			gray							
DK_PG-13,5-C/1	13,5	20,3	black	9	5	25	23	24	13	6,7-12
DK_PG-13,5-S/1			gray							
DK_PG-16-C/1	16	22,3	black	10	5,5	28	26,5	26,5	15,5	10,2-14
DK_PG-16-S/1			gray							
DK_PG-21-C/1	21	28,3	black	10	6	35	32,5	32,5	19,5	13-18
DK_PG-21-S/1			gray							
DK_PG-29-C/1	29	37	black	11	6,5	45	41	41,5	26,8	18,5-25
DK_PG-29-S/1			gray							
DK_PG-36-C/1	36	47	black	14	7,2	58	51,6	51,3	34,3	23-32
DK_PG-36-S/1			gray							
DK_PG-42-C/1	42	53	black	14	8	63,7	58,5	58,5	40	32,7-38
DK_PG-42-S/1			gray							
DK_PG-48-C/1	48	58,5	black	14	8	69	64	64	45	37-44
DK_PG-48-S/1			gray							