

**R 50 Hand press**



Press for terminals and connectors:

- without insulation (except cable end-sleeves) (SA dies) of 10 ÷ 50 mm<sup>2</sup>
- with insulation (except cable end-sleeves) (SE dies) of 10 ÷ 50 mm<sup>2</sup>
- cable end-sleeves with and without insulation (ST dies) of 25 ÷ 120 mm<sup>2</sup>
- Cu tubular on cable conductors (SD dies) of 6 ÷ 50 mm<sup>2</sup>
- Al tubular on cable conductors (SD dies) of 16 ÷ 50 mm<sup>2</sup>

Crimping dies need to be ordered separately.

Length: 575 mm; Weight: 2,7 kg

Type of die	Terminals and connectors	Description	Form of crimping
SA		For Cu ring terminals without insulation of 10 ÷ 50 mm <sup>2</sup> .	
SE		For Cu terminals and connectors with insulation (except cable end-sleeves) of 10 ÷ 50 mm <sup>2</sup> .	
ST		For Cu cable end-sleeves with and without insulation of 25 ÷ 120 mm <sup>2</sup> .	

Type of die	Terminals and connectors	Description	Form of crimping
SD		For Cu tubular terminals and connectors of 6÷50 mm <sup>2</sup> . For Al tubular terminals and connectors of 16÷50 mm <sup>2</sup> .	

Type of die	Discriminant	Terminals – cross section [mm <sup>2</sup> ]				
		DIN Cu tubular	Others Cu tubular	DIN Al tubular	ARC, ALC Thin-walled Al tubular	ARG, ALG, AFG Thick-walled Al tubular
SD	6	10	6			
	7		10			
	8	16	16			
	9				16	
	10	25	25		25	
	12	35	35	16;25	35	16
	14	50	50	35	50	25