


TSE Tab

for multi-wire Cu cables



With copper tube and polyamid insulation

Thermal resistance: -40°C to +125°C

Material: brass

Made according DIN 46248

| Nominal wire cross section [mm ²] | Cross section [mm ²] | Symbol | s [mm] | l ₁ [mm] | l _{2min} [mm] | b [mm] | a _{min} [mm] | d ₂ [mm] | d ₃ [mm] | Weight [g/pce] | Unit [pcs] | Crimping tools |
|---|----------------------------------|-----------|--------|---------------------|------------------------|--------|-----------------------|---------------------|---------------------|----------------|------------|-----------------------------|
| 1 | > 0,5 ÷ 1 | TSE 6,3-1 | 0,8 | 21 | 8 | 6,3 | 4,5 | 1,6 | 3,2 | 0,82 | 100 | |
| 2,5 | > 1 ÷ 2,5 | TSE 6,3-2 | 0,8 | 21 | 8 | 6,3 | 4,5 | 2,3 | 3,8 | 1,01 | 100 | PR33, E11-6, RE6, PP8, PP19 |
| 6 | > 2,5 ÷ 6 | TSE 6,3-6 | 0,8 | 21 | 8 | 6,3 | 4,5 | 3,4 | 5,2 | 1,39 | 100 | |

Standard production –tinned.

VO class insulation on request – symbol e.g. TSE 6,3-1-VO.