

Presseinsätze ZS



Rohrkabelschuhe und Verbinder Cu 6 ÷ 300 mm², Al 16 ÷ 240 mm².

Press-einsatz	Kennziffer	Kabelschuhtypen - Querschnitt				
		Rohrkabel- schuhe Cu nach DIN	Rohrkabel- schuhe Cu nicht genormt	Rohrkabel- schuhe Al nach DIN	Rohrkabel- schuhe dünnwändig ARC, ALC	Rohrkabel- schuhe dickwändig ARG, ALG, AFG
ZS	6	10	6			
	7		10			
	8	16	16			
	9				16	
	10	25	25		25	
	12	35	35	16;25	35	16
	14	50	50	35	50	25
	16	70	70	50	70	35
	18	95	95	70	95	50
	19		120			
	20	120			120	70
	22	150	150	95;120	150	95
	23		185		185	
	25	185	240	150		120
	28	240		185	240	150
	30		300			185
	32	300		240		

Die Pressbreite des Presseinsatzes ZS für Kupfer und Aluminium - 7mm.

■ Basisset ZS_K8 für Kabelschuhe genormt nach DIN – 12 Größen.

■ Erweitertes Set ZS_K-K7 – 17 Größen.




Verbindungsmaterial



KCR

Pressform



Werkzeuge



PRZ 240



HRZ 300



EPZ 300N



EPZC 300



GZ 300