## **SERKO**®



## Increase efficiency by 100% - H 800 pump



## H 800 pump

New H 800 foot pump was designed considering our customers' needs. Two circuits hydraulics, increasing its efficiency by 100%, enable faster action. Use of new materials made the pump lighter (in comparison to previous version), despite the larger oil tank. Due to increased oil volume wider range of tools can work with the pump. Special attention was paid to ergonomics and functionality. We managed to achieve that by decreasing pump's weight, as well as improving ergonomics of foot lever. The tool delivered to our customers is one of most compact among offered on the market. Bearing in mind quality and reliability of the device we applied known and tested solutions of H 700 pump, well rated by our customers.

We offer new H 800 pump in three versions. Basic version with working pressure of 630 bar and two-meter hydraulic hose with PT quick coupler. Version with manometer enabling visual inspection of processes, as well as detection of any incorrectness. Most extended version is pump with manometer and automatic oil release, when working pressure is achieved, actuator automatically returns to starting position.

## Special features:

- two circuits efficient work: at low pressure 13,7 cm<sup>3</sup>/stroke at high pressure 1,3 cm<sup>3</sup>/stroke
- working pressure 630 bar
- oil tank capacity 550 ml
- dimensions (LxWxH): 500x170x150mm
- weight: 8,4 kg



